

System Control

Embedded Windows platform

Intel® Xscale® processor
Microsoft® Windows® CE

Customer Display

10.4" TFT LCD

Communication

Dial-up or
TCP/IP (SSL configurable)

Input Type

4 x 2 Function keys
4 x 4 Numeric keys
VISA/PCI EPP (Encrypting PIN pad)
ADA compliant

Card Handling

Dip type card reader

Optional

IC card reader
EMV Level 1, 2

Cash Dispensing

1000 notes cassette
2000 notes cassette (Up to 3 Cassettes)

Printers

3.1" Graphical thermal receipt printer
Electronic journal
Optional Journal printer

Security

UL291 Business hour
Standard electronic safe lock
Optional KABA Mas Cencor safe lock

Miscellaneous

Lead-through indicator
Optional high brightness topper

Power Supply

AC 110 - 230V, 50 - 60Hz

Operating Environment

Temperature
32°F - 104°F (0°C - 40°C)
Humidity
25% - 86%

Dimension and Weight

Height : 53.5" (1,360mm)
Width : 15.7" (400mm)
Depth : 24.8" (631mm)
Weight : 253.5 lbs (115kg)
(when Monimax 5000CE 1K CDU equipped)

Ⓢ New technologies and components may be implemented in the products without prior notice, so Nautilus Hyosung reserves the right to change specifications accordingly.

