

System Control

Intel® Pentium® -IV processor
Microsoft® Windows® XP platform
15" TFT LCD

Optional

12.1" TFT LCD

Communication

TCP/IP (SSL configurable)

Optional

Dial up, Wireless connection

Application Software

NDC+, DDC912, Web enabled

Customer Display

15" Color TFT LCD
Sunlight viewable

Input Type

4 x 2 Function Keys
4 x 4 Numeric keys
VISA EPP (Encrypting PIN Pad)
DES, T-DES, Mac
ADA compliant

Optional

Touch screen

Card Handling

Dip type card reader

Optional

IC card reader
EMV Level 1&2 compliant

Cash Dispensing

2000 notes Cassette
(Up to 3 Cassettes)

Printers

Graphic thermal receipt printer
Electronic journal

Optional

Graphic thermal journal printer

Security

UL291 Business hour safety
Electronic lock
Security camera

Optional

KABA Mas Cencon safe lock

Miscellaneous

Lead-through indicator
Backup battery
(Reserving last transaction and safety shutdown)

Optional

High brightness topper

Side-car (Optional)

HK300

Bill acceptor
Card dispenser
Card printer

HK400

Check scanner
Finger print scanner
Coin acceptor (Optional)
Coin dispenser (Optional)
Card dispenser
ID card scanner

Power Supply

AC 110 - 230V, 50 - 60Hz
Backup battery
(Reserving last transaction and safe shutdown)

Operating Environment

Temperature
32°F - 104°F (0°C - 40°C)
Humidity
25% - 85%

Dimension and Weight

Height : 51.2" (1,300mm)
Width : 16.1" (410mm)
Depth : 22.8" (580mm)
Weight : 265 lbs (120kg)

ⓘ New technologies and components may be implemented in the products without prior notice, so Nautilus Hyosung reserves the right to change specifications accordingly.

